

The Blackstone fireplace has a large front opening to highlight the stacked brick interior and offers a full view of the fire on those cold winter nights.

STANDARD FEATURES


- Available in 36" and 42" models
- * Radiant smooth-faced or circulating rolled louver models
- Fully insulated firebox
- White stacked refractory panels
- Push/pull damper control
- Includes mesh fire screens & log grate
- Barometric outside air damper
- Fan kit available (for circulating models only)
- Durable textured powder coat finish
- Uses IHP 8 DM (1700°) double wall air cooled wood burning chimney
- 20 year limited warranty

LINER




White Stacked





	BLACKSTONE 36	BLACKSTONE 42
WIDTH	38-1/4"	44-1/4"
HEIGHT	38-5/8"	37-5/8"
DEPTH	22"	22"



	BLACKSTONE 36	BLACKSTONE 42
A	22-1/2"	28-1/2"
В	21-1/8"	21-1/8"
C	38"	44"
D	36"	42"
E	21-1/2"	21-1/2"
F	34"	33"
G	13-7/8"	10-3/8"
Н	9-1/8"	8-1/4"
I	9-5/8"	7"
J	10-1/4"	13"



ADDITIONAL ACCESSORIES

OUTSIDE AIR KIT

GAS LOGS

IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation, wind, vent configuration and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, climate, condition and type of fuel used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.

Diagrams, illustrations and photographs are not to scale—consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.





