



Model DV21
18,000 BTU's

Units can be mounted to any outside wall for direct venting.

Lighting made easy with the matchless piezo ignition

Automatic shutoff and thermocouple safety valve. Built in thermostat with one dial control.



Model DV8
7,500 BTU'S

Models are available in NG or LP gas

SPECIFICATIONS

Models		DV8	DV21
Combustion		Atmospheric Burner	
Standard Heating Space		72-255 Sq. Ft.	169—529 Sq. Ft.
External Dimensions Inches	Height	24 5/64"	
	Width	12 15/64"	25 19/32"
	Depth	5 1/32"	7 1/32"
Net Weight Lbs.		21.2 lbs	53.2 lbs.
Max Gas consumption		7,500 Btu/hr.	18,000 Btu/hr.
Test Point Pressure	Natural Gas	3.5" W.C.	
	Propane/LP	10.0" W.C.	
Safety Devices		Safety Valve (Thermocouple)	

HIGH ALTITUDE SPECIFICATIONS

For altitudes/elevations above 2,000 Ft. (610 m), input ratings should be reduced at the rate of 4 percent for each 1,000 feet (305 m) above sea level. Canadian high altitude for locations having an elevation above mean sea level between 2,000 feet (610 m) and 4,500 feet (1,370 m), use orifices as indicated in the following table:

Model	0-2,000 feet (0-610m)		2,000-4,500 feet (610-1,370m)	
	Main Burner Orifice/Gas Pressure		Main Burner Orifice/Gas Pressure	
	Natural Gas	LP Gas	Natural Gas	LP Gas
DV8	1.35mm/3.5"	.85mm/10.0"	1.27mm/3.5"	0.83mm/10.0"
DV21	2.26mm/3.5"	1.30mm/10.0"	1.83mm/3.5"	1.27mm/10.0"