

ZVF24

ZERO CLEARANCE **VENT-FREE** GAS FIREPLACE





Vent-Free appliances can only be installed in some areas of the United States.

2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

Model Fuel Input Max. Input Min. **Gas Control** ZVFB2410MVN* Natural 10,000 BTU

Millivolt

ZVFB2410MVP* Propane

10.000 BTU

Millivolt

ZVFB2426MVN **Natural** 25.250 BTU 17,500 BTU Millivolt

ZVFB2426MVP Propane 24.250 BTU 19,000 BTU Millivolt

STANDARD FEATURES

- Millivolt Valve System
- An ODS sensor that constantly monitors the room air and provides 100% gas shut off if oxygen is reduces below acceptable levels
- Black Canopy Hood
- Pull Screen
- Matchless Piezo Ignition
- On/Off Rocker Switch
- Decorative Ash Bed

OPTIONAL FEATURES

Fan Kit

Heat activated with variable speed control

Black Arch Doors

Deluxe and Double Door

Designer Picture Frame Surround

Black, Coverage 25" w x 29" h

Brick Refractory Liner

Traditional, Herringbone

Wall Mount Thermostat

Standard On/Off or Programmable 5 day (weekday) and 2 day (weekend)

Remote Control

On/Off, Thermostat on/off, Thermostat On/Off modulating,





Brick Liner RLT



Herringbone Brick Liner RLH

Model ZVF24 Vent-Free Firebox with ZVFB2426MVN Vent-Free Burner System (Natural Gas) LOGF10 Log Set, ZVF24RLT Brick Liner (Traditional), ZVF24SDBL Surround Deluxe (Black), ZVF24ADDD Arch Door, Double Door.

UNIT AND FRAMING SPECIFICATIONS (IN.)

Model Actual	Framing	Actual	Framing	Actual	Framing	
ZVF24 29 ¹⁵ / ₁₆ "	30″	24"	243/8"	131/16"	123/4"	۰





arately to create a complete unit. Discuss with your local Kingsman dealer for clarificatic of continuous testing, refinement and improvements of all its products. Some aspect of un gation. Certification: The model ZVF24 is certified for USA as a Vent-Free Gas Fireplace He



FOR CALIFORNIA RESIDENTS ONLY:

