



## SAMPLE SPECIFICATION PELLET CHIMNEY

### PART 1 GENERAL

#### 1.1 SCOPE

- A. The provisions of Section \_\_\_\_\_, Mechanical General Specifications apply to all work in this Section.
- B. This section includes specifications for furnishing and installing Pellet Chimney.

#### 1.2 SUBMITTALS

Submit the following in accordance with Section \_\_\_\_\_:

- A. Catalog cuts
- B. Installation drawings
- C. Installation instructions
- D. Sample of warranty

### PART 2 QUALITY ASSURANCE

#### 2.1 APPLICABLE STANDARDS

Pellet Chimney products furnished under this Section shall be listed to UL-641 and shall carry the appropriate UL listing mark or label.

#### 2.2 WARRANTY

Pellet Chimney shall be warranted by the manufacturer against defects in material and workmanship for a period of ten (10) years from the date of the original installation.

## PART 3 PRODUCTS

### 3.1 PELLET CHIMNEY

- A. The Pellet Chimney shall be of factory-built double-wall construction, using stainless steel flue and galvanized outer casing.
- B. The Pellet Chimney shall be constructed of an outer wall of .018" thick Galvanized steel and an inner wall of .012" thick stainless steel.
- C. The pipe sections shall have a rope gasket at each joint to prevent fly ash leakage.
- D. All sizes of Pellet Chimney shall include an integral, annular air space of ¼".
- E. The double-wall Pellet Chimney shall be tested and listed for a minimum clearance to combustibles of 3".
- F. All fittings, supports, flashing, storm collar, and termination required to install the Pellet Chimney shall be included.
- G. Pellet Chimney shall be Model P as manufactured by Metal-Fab Inc.
- H. Pellet Chimney shall be installed in accordance with the chimney manufacturer's installation instructions, UL listing, and state or local codes.

