

FLEXI-LINER®

**Flexible Aluminum
Chimney Liner Kits**

Specifications

APPLICATION:

- ⚠ Chimney Liner for Category I gas fired appliances approved for use with B-Vent or appliances equipped with draft hoods

APPROVALS:

- ⚠ USA: UL 1777 Chimney Liners
- ⚠ CANADA: ULC S635 Liners for Existing Masonry and Factory-Built Chimneys and Vents

SPECIFICATIONS:

- ⚠ Liner Material..... Aluminum 3003, 2-ply (0.005" each)
- ⚠ Maximum Flue Gas Temperature..... 470° F
- ⚠ Available Size Range..... 3" – 8" dia.
(Larger sizes available as Special Order)
- ⚠ Standard Kit Lengths..... 25' and 35' (15' Kits available for 3", 4", 5")
- ⚠ Stretch Ratio..... 5:1 (approx.)
- ⚠ Clearances..... 0" between liner and chimney interior
0" between combustible materials & chimney exterior
- ⚠ Warranty..... "Smart Choice" Lifetime Warranty

KIT CONTENTS:

Flexi-Liner Kits Include:
Flexi-Liner Length
Round Top
Top Adapter
Flashing: w/3" Collar
Mortar Guard
Fasteners
Instructions/Warranty

OPTIONAL ACCESSORIES:

- Flexi-Extension Kits Flexi-Liner Tube w/attached coupler & fastener pkg
- Flexi-Sleeve Insulation sleeve w/tough poly exterior
- Flex Coupler Fitting w/rivets for joining Flexi-Liner sections
- Pull Down Tool to stretch & lead Flexi-Liner Tube down chimney
Assists pulling Flexi-Sleeve over Liner
- B-Vent Adapter Fitting to adapt Flexi-Liner to all brands of Type B-Vent



375 Green Road,
Stoney Creek, ON L8E 4A5
Toll Free: 1.888.SELKIRK (735.5475)
www.selkirkcanada.com

1301 W. Pres. George Bush Highway
Richardson, TX 75080-1139
Toll Free: 1.800.992.VENT (8368)
www.selkirkusa.com