

WARM UP TO A VISTAFLAME



Specifications	VF100 FS & FPI	
Maximum Heat Output*	45,000 BTU	
Minimum Heat Output*	10,000 BTU	
Heating Area	2,200 ft ²	
Efficiency*	82%	
Hopper Capacity	55 lbs	
Glass Size	185 in²	
Power (normal use / start up)	250/520 watts	
Variable Fan Speed	160 cfm	

^{*} Efficiency, emissions and area heated will vary according to fuel type, venting and location


Clearance to Combustibles

Side wall to unit — FS & FPI	6''	8''
Rear wall to back of unit — FS	1"	_
Adjacent wall to corner — FS	1"	_
Floor Protection in front — FS & FPI	6''	6''
Top of unit to mantle — FPI	_	8''

VF100 Features

- Large heat exchanger
- Easy access hopper
- Steel brick firebox liner
- Large ash pan
- Standard ignitor
- Hidden door handle
- Fireplace surround (FPI only)
- Mobile home approved
- Automatic controls

22"



More detailed measurements available in product manual

VF100 Options

- Wireless Digital Thermostat or Remote Control An optional wireless digital Wall Thermostat and remote control are available for the VF100.
- Trim Variety Painted black, and brushed nickel.
- Oversized Surround—FPI model only.



Manufactured by Sherwood Industries Ltd Victoria, BC, Canada • vistaflame.ca Printed in Canada, January 2013